

## Disc, Bolt & Spacer fitting chart

### 996 GT3 MK1

Front (standard 330mm disc):	Bolt = 77mm	
To fit Alcon 362mm disc	Bolt = 95mm	Spacer = 16mm
Rear (standard 330mm disc)	Bolt = 77mm	
To fit Alcon 350mm+PCCB bell	Bolt = 85mm	Spacer = 10mm
To fit Alcon 360mm disc	Bolt = 90mm	Spacer = 15mm

### 996 GT3 MK2

Front (standard 350mm disc):	Bolt = 85mm	
To fit Alcon 362mm disc	Bolt = 90mm	Spacer = 6mm
Rear (standard 330mm steel disc)	SEE 996 GT3 MK1	
Rear (PCCB 350mm disc):	Bolt = 85mm	
To fit Alcon 350mm+PCCB bell	Bolt = 85mm	Spacer = NONE
To fit Alcon 360mm disc	Bolt = 90mm	Spacer = 5mm

### 996 GT2 MK1&2 (all cars were 350mm PCCB F & R)

Front (PCCB 350mm disc):	Bolt = 85mm	
To fit Alcon 362mm disc	Bolt = 90mm	Spacer = 6mm
Rear (PCCB 350mm disc):	Bolt = 85mm	
To fit Alcon 350mm+PCCB bell	Bolt = 85mm	Spacer = NONE
To fit Alcon 360mm disc	Bolt = 90mm	Spacer = 5mm

996 Turbo (On original 4-pot calliper) - Same as 996 GT3 MK1

996 Turbo S (PCCB) - Same as 996 GT3 MK2

## 997 GT3 Gen1

Front (Steel 350mm disc):	Bolt = 85mm	
To fit Alcon 362mm disc	Bolt = 90mm	Spacer = 6mm
Front (PCCB 380mm disc):	Bolt = 62mm	
To fit Alcon 380mm disc	Bolt = 62mm	Spacer = NONE
Rear (350mm disc):	Bolt = 95mm	
To fit Alcon 360mm disc	Bolt = 100mm	Spacer = 5mm

## 997 GT3 Gen2

Front (380mm disc):	Bolt = 62mm	
To fit Alcon 380mm disc	Bolt = 62mm	Spacer = NONE (NO PARTS NEEDED)
Rear (350mm disc):	Bolt = 95mm	
To fit Alcon 360mm disc	Bolt = 100mm	Spacer = 5mm

## 997 GT2 / GT2RS

Front (380mm disc):	Bolt = 62mm	
To fit Alcon 380mm disc	Bolt = 62mm	Spacer = NONE (NO PARTS NEEDED)
Rear (350mm disc):	Bolt = 95mm	
To fit Alcon 360mm disc	Bolt = 100mm	Spacer = 5mm

## 997 Turbo Gen1 & Gen2

Front (Steel 350mm disc):	Bolt = 85mm	
To fit Alcon 362mm disc	Bolt = 90mm	Spacer = 6mm
Front (PCCB 380mm disc):	Bolt = 62mm	
To fit Alcon 380mm disc	Bolt = 62mm	Spacer = NONE (NO PARTS NEEDED)
Rear (350mm disc):	Bolt = 95mm	
To fit Alcon 360mm disc	Bolt = 100mm	Spacer = 5mm